



Architectural Concrete Chemicals

223 West Hampton Avenue

Capitol Heights, MD 20743

(301) 336-9300 • Fax (301) 336-6597

www.acchemicals.com

Pre-Cote Fast Dry

PRODUCT DESCRIPTION: Pre-Cote Fast Dry is an innovative undercoat release for use in conjunction with ACC Altus Series retarders. It is a white colored hydrophilic (water utilizing) film that dries completely in 5-15 minutes depending upon ambient conditions.

AREA OF APPLICATION: Perfectly suited for architectural precast concrete of all types,

DIRECTIONS: Apply Pre-Cote Fast Dry to the mold surface in a thin coat by brush or by roller at a rate of 400-500 sq. ft./gal. Pre-Cote Fast Dry dries in 10-20 minutes depending upon ambient conditions. When dry, proceed with the selected grade of Altus Series high performance in-form retarder.

TECHNICAL DATA: Solubility in water: soluble. Appearance and odor: Opaque white with alcohol odor. Specific Gravity 1.2. % Volatile by volume 95%. Flash point 53° F by TCC, boiling point 83° C.

SHELF LIFE AND STORAGE: One year from manufacturing date in closed original container.

PACKAGING: 5-gal steel pails, 55-gal steel drums

SAFETY: Highly flammable. Keep away from heat, sparks and open flames. Use respirator for spray applications.

SHIPPING CLASSIFICATION: UN1219, Isopropanol Solution, 3, PG:II